

TECHNICAL SHEET

valid from 1.1.2014

review 1.1.2016

PRODUCT NAME:	MONACO
APPLICATION:	LANDSCAPING
MATERIAL:	PILE: PE monofilament – lens profile (straight + texturized)
	PRIM. BACKING: 100% PP
	SECONDARY BACKING: SBR Latex
GAUGE:	3/8"
COLOR:	bicolor green, bicolour brown (olive green/field green + dark brown/sand)

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness-straight	[dtex]	7.200/8	± 10%
Pile width	[mm]	0,9	± 10%
Pile thickness	[µm]	170	± 10%
Pile fineness-texturized	[dtex]	7.800/8	± 10%
Pile width	[mm]	0,9	± 10%
Pile thickness	[µm]	170	± 10%
Pile weight per unit area	[g/m ²]	1.753	± 10%
Stitch rate per 10 cm (length)	[-/10 cm]	14	± 10%
Number of tufts/m ²	[-/m ²]	14.698	± 10%
Number of piles/m ²	[-/m ²]	470.336	± 5%
Pile height	[mm]	35	± 5%
Weight primary backing	[g/m ²]	170	± 10%
Weight secondary backing	[g/m ²]	700	± 10%
Total weight	[g/m ²]	2.623	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,00; 2,00	± 0,02

COMMENTS:

Recommended infill: non filled

In case of free installation without mechanical fixing or bonding may the turf due to climatic changes shrink up to 1%. This product is not designed for frequently walking areas.

Any supplementary information and certificates are available upon request at our sales department. According to the Regulation (EC) No 1907/2006 (REACH), this product does not contain any dangerous substances.

JUTA a.s. reserves the right to amend the technical specifications of the above mentioned product. The delivered product may slightly differ from these data. JUTA a.s. guarantees the technical quality of the product.



JUTA a.s., Dukelská 417
Dvůr Králové nad Labem
544 15
Česká republika
www.juta.cz

www.jutagrass.com

JUTAgass, Na Borkách 89
Dvůr Králové nad Labem
Tel.: +420 499 314 567
Fax: +420 499 314 572
e-mail: jutagrass@juta.cz